BREL International

CHM-Series
Precision High-Value Chip Resistors
Sizes: 0805, 1206, 1210, 2010, 2512, 4020

Features:

- Meander structured high value chip resistors in thick film technology
- Low temperature and voltage dependency
- Suitable for high vacuum applications – no organics
- Termination: PtAg [0)] for conductive glueing and soldering
- High working voltage up to 6000 V
- High temperature application up to 300°C possible (CHM-HT)
- Non-magnetic

RoHS / ELV conform 2011/65/EC 2000/53/EC

e4

Non-Magnetic

Dimensions:

Size		L (mm)	B (mm)	D (mm)	C (mm)
Imperial (Standard)	Metric (ref. only)	length	width	thickness	width of wrap around
0805	2012	2.00 +0.15/-0.05	1.25 +0.15/-0.05	0.40 +0.15/-0.05	0.3 +0.2/-0.1
1206	3216	3.20 +0.15/-0.05	1.50 +0.2/-0.05	0.40 +0.15/-0.05	0.3 +0.2/-0.1
1210	3225	3.20 +0.15/-0.05	2.50 +0.2/-0.05	0.50 +0.15/-0.05	0.8 ±0.2
2010	5025	5.10 +0,15/-0,05	2.50 +0,2/-0,05	0.60 +0,20/-0,1	0.9 ±0.2
2512	6332	6.30 +0.15/-0.05	3.50 +0.2/-0.05	0.60 +0.15/-0.05	0.9 ±0.2
4020	10050	10.20 +0.20/-0.05	5.10 +0.2/-0.05	0.60 +0.20/-0.1	0.9 ±0.2



Packaging:

Bulk in plastic bags – minimum quantity 30 pieces per value
Embossed carrier tape acc. to IEC 60286-3 – minimum 500 pieces per value
Reel diameter 180 mm or 330 mm

Ordering Data:

Type – value – tolerance – Temperature coefficient TCR
Example: *CHM 2512 10G ±10% TCR100*

Untrimmed parts are indicated by the extension "*NA*" in the order code:
Type – value – tolerance – NA – Temperature coefficient TCR
Example: *CHM 2512-NA 10G ±10% TCR100*

Without requirement for the temperature coefficient TCR, the standard value (highest value in table) will be supplied. Standard measuring voltage is 10V. Different voltages on request and agreement (specify explicitly).

[0)] PtAg: Platinum-Silver thick film

BREL International
2001 Whitfield Park Ave
Sarasota, FL 34243 USA

Phone: + 1-941-758-7500
Fax: +1-941-758-7556
Mail: sales@brelintl.com
Web: www.brelintl.com

BREL International

CHM-Series
Precision High-Value Chip Resistors
Sizes: 0805, 1206, 1210, 2010, 2512, 4020

Technical data – depending on size:

Size	0805	1206	1210	2010	2512	4020
Power rating P_{70} (mW) (P_{155} = 0 mW)	125	250	350	750 [2]	1000 [2]	2000 [2]
Max. working voltage (V) [1] Standard (trimmed) NA (untrimmed, Tol. ≥ 5%)	 200 400	 600 1000	 800 1200	 1500 2000	 2500 3000	 4000 6000
Ranges / Tolerances / Temperature coefficient TCR [3] / VCR [4]						
100K – 100M	0.5/1/2/5/10% TCR25/50/100 100 ppm/V	0.5/1/2/5/10% TCR25/50/100 50 ppm/V	0.5/1/2/5/10% TCR25/50/100 50 ppm/V	0.5/1/2/5/10% TCR25/50/100 25 ppm/V	0.5/1/2/5/10% TCR25/50/100 10 ppm/V	0.25/ … /10% TCR25/50/100 5 ppm/V
>100M – 1G	2/5/10/20% TCR50/100/250 250 ppm/V	2/5/10/20% TCR50/100/250 100 ppm/V	1/2/5/10/20% TCR25/50/100 50 ppm/V	1/2/5/10/20% TCR25/50/100 50 ppm/V	1/2/5/10/20% TCR25/50/100 25 ppm/V	0.5/ … /20% TCR25/50/100 10 ppm/V
>1G – 10G	5/10/20% TCR250/500 500 ppm/V	5/10/20% TCR100/250 250 ppm/V	2/5/10/20% TCR25/50/100 100 ppm/V	2/5/10/20% TCR25/50/100 100 ppm/V	2/5/10/20% TCR25/50/100 50 ppm/V	1/2/5/10/20% TCR25/50/100 10 ppm/V
>10G – 100G	10/20/30% TCR1000/2000 1000 ppm/V	10/20/30% TCR500/1000 500 ppm/V	5/10/20/30% TCR500/1000 500 ppm/V	5/10/20/30% TCR250/500 250 ppm/V	5/10/20/30% TCR100/250/500 100 ppm/V	2/5/10/20/30% TCR50/100/250 50 ppm/V
>100G – 1T	20/30% TCR2000 3000 ppm/V	10/20/30% TCR1000/2000 1000 ppm/V	5/10/20/30% TCR1000/2000 1000 ppm/V	5/10/20/30% TCR500/1000 500 ppm/V	5/10/20/30% TCR250/500 250 ppm/V	5/10/20/30% TCR250/500 100 ppm/V
>1T – 3T	–	on request	on request	on request	10/20/30% TCR2000 1000 ppm/V	10/20/30% TCR1000 500 ppm/V
>3T – 10T	–	-	-	on request	10/20/30% TCR3000 2000 ppm/V	10/20/30% TCR2000 1000 ppm/V

[1] Continuous operating voltage (U_, U_{eff}): $V \leq \sqrt{(P*R)}$ or max. working voltage (the lower value)
[2] At continuous power dissipation the dimensions of solder-pads have to secure a sufficient heat removal
[3] Temp. coeff. TCR: in ppm/K; +25°C...+125°C; TCR lower than standard TCR (highest value) or R >100G: +25°C...+85°C
[4] VCR: typical values, all negative, not for all temperature coefficient values available
Lower values of tolerance, Temperature coefficient TCR and VCR on request and agreement only

Technical data – general:

Operating temperature range	-55°C ... +155°C
Climatic category acc. to EN 60068-1	55/155/56
Solderability acc. to EN 60068-2-58 (lead-free and lead-containing) [5]	250°C, 3s
Max. soldering temperature acc. to EN 60068-2-58	260°C, 10s
Moisture Sensitivity Level acc. to J-STD-020	MSL 1 (unlimited)

Extended temperature range up to 300°C: see datasheet “High temperature chip resistors” CHM-HT

Long term stability	< 1G	< 10G	≥ 10G
Load Life 70°C/1000h	< 0.25%	< 0.5%	< 1%
Storage 125°C/1000h	< 0.5%	< 1%	< 2%
Max. voltage/1000h	< 0.5%	< 1%	< 2%

[5] Up to 6 months after shipment (air, 30°C/60%rH) or up to 12 months at storage in Nitrogen or in evacuated dry packs.
Other data according to EN 140401-802 (CECC 40401-802).

BREL International
2001 Whitfield Park Ave
Sarasota, FL 34243 USA

Phone: +1-941-758-7500
Fax: +941-758-7556
Mail: sales@brelintl.com
Web: www.brelintl.com